MRS Communications

MRS Communications March 2012 2 : pp 9-12
 Copyright © Materials Research Society 2011
 DOI: <http://dx.doi.org/10.1557/mrc.2011.24> (About DOI)
 Published online by Cambridge University Press: November 2011

Table of Contents - March 2012 - Volume 2

Rapid Communications

Phase stability of silicon during indentation at elevated temperature: evidence for a direct transformation from metallic Si-II to diamond cubic Si-I

S.K. Bhuyan^{a1}, J.E. Bradby^{a1 c1}, S. Ruffell^{a1}, B. Haber^{a1}, C. Saint^{a1}, J.S. Williams^{a1} and P. Munroe^{a2}

^{a1} Department of Electronic Materials Engineering, Research School of Physics and Engineering, Australian National University, Canberra, ACT 0200, Australia

^{a2} Electron Microscope Unit, University of New South Wales, Sydney, NSW 2052, Australia

Abstract

Nanoindentation-induced phase transformations in both crystalline silicon (c-Si) (100) and ion-implanted amorphous silicon have been studied at temperatures up to 200 °C. The region under the indenter undergoes rapid volume expansion at temperatures above 125 °C during unloading, which is indicated by "bowing" behavior in the load-displacement curve. Polycrystalline Si-I is the predominant end phase for indentation in crystalline silicon whereas high-pressure Si-III/Si-XII phases are the result of indentation in amorphous silicon. We suggest that the Si-II phase is unstable in a c-Si matrix at elevated temperatures and can directly transform to Si-I during the early stages of unloading.

(Received August 29 2011)

(Accepted November 03 2011)

Correspondence:

^{c1} Address all correspondence to J.E. Bradby at jodie.bradby@anu.edu.au