MATERIALS RESEARCH SOCIETY
SYMPOSIUM PROCEEDINGS VOLUME 957

Zinc Oxide and Related Materials

Symposium held November 27–30, 2006, Boston, Massachusetts, U.S.A.

EDITORS:

Jürgen Christen

Otto-von-Guericke-Universität Magdeburg
Magdeburg, Germany

Chennupati Jagadish

Australian National University
Canberra, Australia

David C. Look

Wright State University
Dayton, Ohio, U.S.A.

Takafumi Yao

Tohoku University
Sendai, Japan

Frank Bertram

Otto-von-Guericke-Universität Magdeburg
Magdeburg, Germany

Materials Research Society
Warrendale, Pennsylvania

Effort sponsored by the Air Force Office of Scientific Research, Air Force Material Command, USAF, under FA9550-07-1-0066. The U.S. Government is authorized to reproduce and distribute reprints for Governmental purposes notwithstanding any copyright notation thereon. The views and conclusions herein are those of the authors and should not be interpreted as necessarily representing the official policies or endorsements, either expressed or implied, of the Air Force Office of Scientific Research or the U.S. Government.

This work was supported in part by the U.S. Army Research Office under Grant Number W911NF-06-1-0430. The views, opinions, and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.

Single article reprints from this publication are available through
University Microfilms Inc., 300 North Zeeb Road, Ann Arbor, Michigan 48106

CODEN: MRSPDH

Copyright 2007 by Materials Research Society.
All rights reserved.

This book has been registered with Copyright Clearance Center, Inc. For further information, please contact the Copyright Clearance Center, Salem, Massachusetts.

Published by:

Materials Research Society
506 Keystone Drive
Warrendale, PA 15086
Telephone (724) 779-3003
Fax (724) 779-8313
Web site: <http://www.mrs.org/>

Manufactured in the United States of America

CONTENTS

Preface	xv
Materials Research Society Symposium Proceedings.....	xvi

DEVICES

* Development of Thin Film and Nanorod ZnO-Based LEDs and Sensors.....	3
S.J. Pearton, L.C. Tien, H.S. Kim, D.P. Norton, J.J. Chen, H.T. Wang, B.S. Kang, F. Ren, W.T. Lim, J. Wright, R. Khanna, L.F. Voss, L. Stafford, J. Jun, and Jenshan Lin	
Ultraviolet Photodetection Properties of ZnO Microtubes	15
Jiping Cheng, Ming Fu, Yunjin Zhang, and Ruyan Guo	

DEFECTS

Temperature Dependent Hall Measurements on PLD Thin Films	23
Holger von Wenckstern, Matthias Brandt, Gregor Zimmermann, Jörg Lenzner, Holger Hochmuth, Michael Lorenz, and Marius Grundmann	
Persistent Photoinduced Changes in Charge States of Donors and Acceptors in Hydrothermally Grown ZnO	29
N.C. Giles, Yongquan Jiang, Xiaocheng Yang, S.M. Evans, and L.E. Halliburton	
Spatially Resolved Study of Magnesium Incorporation in Zn _{1-x} Mg _x O Nanostructures	35
Martin Schirra, Anton Reiser, Günther Michael Prinz, Raoul Schneider, Rolf Sauer, and Klaus Thonke	
Electrical Characterization of Proton Irradiated n-Type ZnO	41
F. Danie Auret, Michael Hayes, Jackie Nel, Walter Meyer, Pieter Johan Janse van Rensburg, Werner Wesch, and E. Wendler	

*Invited Paper

SPINTRONICS AND MAGNETISM

Electrical and Magnetic Properties of Doped ZnO Nanowires.....	4
Gennady N. Panin, Andrey N. Baranov, Tae Won Kang, Oleg V. Kononenko, Sergey V. Dubonos, S.K. Min, and H.J. Kim	
Transition Metal-Doped ZnO: A Comparison of Optical, Magnetic, and Structural Behavior of Bulk and Thin Films	5
William E. Fenwick, Matthew H. Kane, Zaili Fang, Tahir Zaidi, Nola Li, Varatharajan Rengarajan, Jeff Nause, and Ian T. Ferguson	
Ferromagnetic Mn-Mn Interactions in Low Doped Zn_{1-x}Mn_xO Thin Films	6
Aroussi Ben Mahmoud, H. Jurgen von Bardeleben, Alain Mauger, Jean-Louis Cantin, Ekaterina Chikoidze, and Yves Dumont	

GROWTH

Growth and Characterization of Homoepitaxial ZnO Thin Films Grown by CVD	69
Christian Neumann, Joachim Sann, Stefan Lautenschläger, Frank Bertram, Jürgen Christen, Jürgen Bläsing, Alois Krost, and Bruno K. Meyer	
Orders of Magnitude Reduction in Threading Dislocations in ZnO Grown on Facet-Controlled GaN	73
Soo Jin Chua, Hai Long Zhou, Hui Pan, and Thomas Osipowicz	
Modification of ZnO Layers by Molecular Adsorbates During Electrochemical Deposition.....	75
Thomas Loewenstein, Christian Neumann, Bruno K. Meyer, Tsukasa Yoshida, and Derck Schlettwein	
The Growth of ZnO on CrN Buffer Layer Using Surface Phase Control by Plasma Assisted Molecular-Beam Epitaxy	85
Jinsub Park, Tsutomu Minegishi, Seunghwan Park, Inho Im, Takahasi Hanada, Soonku Hong, Takenari Goto, Meoung-Whan Cho, and Takafumi Yao	

OPTICAL PROPERTIES, NANOSTRUCTURES

Cathodoluminescence Study of Indented ZnO Crystals.....	95
Julio Mass, Manuel Avella, Juan Jiménez, Tomás Rodríguez, Michael Callahan, E. Grant, K. Rakes, David Bliss, and Buguo Wang	

Structural and Optical Studies of Multi Shape ZnO Nanostructures Grown by Direct Vapor Phase Technique.....	101
S.S. Hullavarad, P.C. Karulkar, R.D. Vispute, R. Heng, and T. Venkatesan	

Growth and Characterization of Optical and Electrical Properties of ZnO Nano- and Microwires	107
Marius Grundmann, Andreas Rahm, Thomas Nobis, Holger von Wenckstern, Christian Czekalla, Jörg Lenzner, and Michael Lorenz	

DOPING

Electrical Characterization of Defect States in Local Conductivity Domains in ZnO:N,As Layers.....	115
Andre Krtschil, Armin Dadgar, Annette Diez, and Alois Krost	

Properties of p-Type ZnO Grown by Oxidation of Zn-Group-V Compounds.....	121
Eliana Kaminska, Ewa Przedziecka, Anna Piotrowska, Jacek Kossut, Piotr Boguslawski, Iwona Pasternak, Rafal Jakiela, and Elzbieta Dynowska	

Donors and Acceptors in Bulk ZnO Grown by the Hydrothermal, Vapor-Phase, and Melt Processes.....	127
David Look	

PROCESSING, TFT

Formation of Nanovoids and Nanocolumns in High Dose Hydrogen Implanted ZnO Bulk Crystals	137
R. Singh, R. Scholz, U. Gösele, and S.H. Christiansen	

Effect of Cryogenic Temperature Deposition of Various Metal Contacts to Bulk, Single-Crystal n-Type ZnO	143
Jon Wright, L. Stafford, B.P. Gila, D.P. Norton, S.J. Pearton, Hung-Ta Wang, and F. Ren	
Schottky Contact Behavior as a Function of Metal and ZnO Surface Polarity	149
M.W. Allen, P. Miller, J.B. Metson, R.J. Reeves, M.M. Alkaisi, and S.M. Durbin	
Microstructure and Electrical Property Correlations in Ga:ZnO Transparent Conducting Thin Films	155
Vikram Bhosle and Jagdish Narayan	
Large Area Multi-Wafer MOCVD of Transparent and Conducting ZnO Films	161
Gary S. Tompa, S. Sun, L.G. Provost, Dan Mentel, D. Sugrim, Philip Chan, Keny Tong, Raymond Wong, and A. Lee	

POSTER SESSION I

Surface Luminescence of Polycrystalline Zinc Oxide Excited by Hydrogen Atoms	171
Michael Sushchikh, Vladislav Styrov, Vladimir Tyutunnikov, and Nick Cordella	
Low Temperature Aqueous Polymeric Precursor Processing of ZnO:Er Using a Glycerol Chelating Agent	177
Uma Choppali and Brian P. Gorman	
Vertically Aligned Single Crystalline ZnO Nanorods Grown by Hydrothermal Synthesis and the Theoretical Model for Predicting the Rod Density	183
Soo Jin Chua, Hong Quang Le, Chuan Beng Tay, Kian Ping Loh, and Eugene Fitzgerald	
Study of the Temperature Dependence of E_2 and $A_1(\text{LO})$ Modes in ZnO	187
Esther Alarcon-Llado, Ramon Cusco, Jordi Ibanez, Luis Artus, Juan Jiménez, Buguo Wang, and Michael Callahan	

ZnO-Sn Bilayer Ultraviolet (UV) Photon Detector With Improved Responsivity	195
Harish Kumar Yadav, K. Sreenivas, and Vinay Gupta	
Two-Dimensional Organization of Single Crystal ZnO Nanopillars	201
Jingbiao Cui and Ursula J. Gibson	
Electrical Characterization of Isotype n-ZnO/n-GaN Heterostructures	207
Yahya Alivov, Xiao Bo, Sena Akarca-Biyikli, Fan Qian, Daniel Johnstone, Olena Lopatiuk-Tirpak, Leonid Chernyak, Cole Litton, and Hadis Morkoç	
A Comparison of the Mechanical Properties and the Impact of Contact Induced Damage in <i>a</i>- and <i>c</i>-axis ZnO Single Crystals.....	213
V.A. Coleman, J.E. Bradby, C. Jagadish, and M.R. Phillips	
Acceptors in ZnO Studied by Photoluminescence	219
Michael A. Reshchikov, James Garbus, Gabriel Lopez, Monica Ruchala, Bill Nemeth, and Jeff Nause	
Controllable Synthesis of ZnO Nanorod Arrays via Simple Solution-Based Method	225
Patcharee Charoensirithavorn and Susumu Yoshikawa	
Interface and Luminescence Properties of Pulsed Laser Deposited $\text{Mg}_x\text{Zn}_{1-x}\text{O}/\text{ZnO}$ Quantum Wells With Strong Confinement	229
Susanne Heitsch, Gregor Zimmermann, Alexander Müller, Jörg Lenzner, Holger Hochmuth, Gabriele Benndorf, Michael Lorenz, and Marius Grundmann	
Raman Scattering Characterization of Implanted ZnO.....	235
Esther Alarcon-Llado, Ramon Cusco, Luis Artus, German Gonzalez-Diaz, Ignacio Martil, Juan Jiménez, Buguo Wang, and Michael Callahan	
Fabrication of ZnO and ZnMgO Thin Films and UV Photodetectors by Mist Chemical Vapor Deposition Method	241
Yudai Kamada, Toshiyuki Kawaharamura, Hiroyuki Nishinaka, and Shizuo Fujita	

A Solution Method for Large-Scale Selective Growth of Aligned ZnO Nanorods	24
Qurashi Ahsanulhaq, Ahmad Umar, Sang Hoon Kim, Yeon Ho Im, and Yoon Bong Hahn	
Controllable Synthesis of ZnO Nanonails by Vapor-Solid Process: Growth Mechanism and Structural and Optical Properties	25
Ahmad Umar, Q. Ahsanul Haq, Sang Hoon Kim, Yeon Ho Im, and Yoon Bong Hahn	
Surface Preparation of Single Crystals for ZnO Homoepitaxy	25
Christian Neumann, Stefan Lautenschläger, Swen Graubner, Niklas Volbers, Bruno K. Meyer, Jürgen Bläsing, and Alois Krost	
Cathodoluminescence Study of Hydrothermal Zn_{1-x}Mg_xO Alloy Crystals	26
Julio Mass, Manuel Avella, Juan Jiménez, Michael Callahan, E. Grant, K. Rakes, David Bliss, and Buguo Wang	
Growth and Characterization of Mg_{0.15}Zn_{0.85}O Thin Films by Pulsed Laser Deposition	27
Wei Wei, Chunming Jin, Anand Doraiswamy, Roger J. Narayan, and Jagdish Narayan	
Visible Luminescence From ZnO Nanostructures	27
An-jen Cheng, Dake Wang, Hee Won Seo, Minseo Park, and Yonhua Tzeng	
A Comparative Study of MOCVD Produced ZnO Films Doped With N, As, P and Sb	28
Gary S. Tompa, S. Sun, C.E. Rice, L.G. Provost, and D. Mentel	
Visible-Light Sensitivity in N-Doped ZnO Films Prepared by Reactive Magnetron Sputtering	28
Yoshitaka Nakano, Takeshi Morikawa, and Takeshi Ohwaki	

POSTER SESSION II

Ferromagnetic Ordering at Room Temperature in ZnO:Co Nanoparticles	297
Sujeet Chaudhary, Kanwal Preet Bhatti, Shankhmala Kundu, Subhash C. Kashyap, and Dinesh K. Pandya	
Structure-Property Relationships in the xZnO-(1-x)alpha-Fe₂O₃ Nanoparticle System	303
Monica Sorescu, Lucian Diamandescu, and Jason Wood	
Opto-Electronic Properties and Stability of Artificial Zinc Oxide Molecules	309
Liudmila A. Pozhar and Gail J. Brown	
Analysis and Applications of ZnO Semiconductor Films Deposited by Laser and Sputtering Techniques.....	315
Tingfang Yen, Meiya Li, Nehal Chokshi, Sung Jin Kim, Alexander N. Cartwright, Yongwoo Jeong, and Wayne A. Anderson	
Optical Properties of Porous ZnO Nanorods Grown by Aqueous Solution Method	321
Sang Hyun Lee, Hyun Jung Lee, Takenari Goto, Meoung-Whan Cho, and Takafumi Yao	
Epitaxial Growth of ZnO Thin Films on SiC Prepared by Chemical Solution Deposition.....	327
Young-Sik Park, Young-Sun Jeon, Kyung-Ok Jeon, Bo-An Kang, Kyu-Seog Hwang, Ju-Hyun Jeong, and Young-Hwan Lee	
Elaboration and Characterization of ZnO Transition Metal (Co, Mn, Ni, Fe) Doped Aerogel Nanoparticles.....	333
Lassaad El Mir, Aroussi Ben Mahmoud, H. Jurgen von Bardeleben, and Jean-Louis Cantin	
Magnetic Properties of ZnO:Ni Aerogel Nanopowders: Effect of Thermal Treatments	339
Lassaad El Mir, H. Jurgen von Bardeleben, M. Saadoun, Aroussi Ben Mahmoud, and Jean-Louis Cantin	
Transport Properties and Conduction Band Offset of n-ZnO/n-6H-SiC Heterostructures.....	347
Yahya Alivov, Xiao Bo, Fan Qian, Daniel Johnstone, Cole Litton, and Hadis Morkoç	

Synthesis and Characterization of Nickel-Doped ZnO Nanocrystals	353
Xiao Li Zhang, Ru Qiao, Yan Li, Ri Qiu, and Young Soo Kang	
Preparation of Shape and Size-Controlled Zinc Oxide Nanostructures by Chemical Spray Pyrolysis Technique	359
Tatjana Dedova, Malle Krunk, Arvo Mere, Jelena Klauson, and Olga Volobujeva	
Influence of the Particle Size on Acoustic Phonon Modes of ZnO Nanocrystals	367
Harish Kumar Yadav, K. Sreenivas, Vinay Gupta, S.P. Singh, B. Sundarakannan, and R.S. Katiyar	
Influence of Annealing Temperature on ZnO Thin Films Prepared by Single and Multi-Step Sol-Gel Processes	373
Lee Huat Kelly Koh, Shane O'Brien, Pierre Lovera, Gareth Redmond, and Gabriel M. Crean	
Electroplating of ZnO Nanowires Using Nanohole Arrays of Anodized Aluminum Oxide and Effects of Thermal Annealing	379
Ken-ichi Ogata, Shoso Shingubara, Hiromi Yorozu, and Tadahiko Nakanishi	
Enhancement of Field Emission Current From ZnO Nanorods Fabricated by Two Step Chemical Vapor Deposition With Laser Ablation of ZnO	385
Takashi Hirate, Takashi Kimpara, Kazumoto Takizawa, and Tomomasa Satoh	
The Impact of Hydrogen Plasma Treatments at Moderate Temperatures on Sintered Zinc Oxide Samples—Evidence for Hydrogen Induced Nano-Void Formation	391
Reinhart Job	
Transport Studies of Transition Metal Ion Doped ZnO: Bulk and Thin Films	397
Shubra Singh, N. Rama, and M.S. Ramachandra Rao	
The Impact of Fermi Pinning on Thermal Properties of the Instabilities in ZnO TFTs	403
R.B.M. Cross and M.M. De Souza	

Optical and Electrical Properties of Gallium-Doped Mg_{0.15}Zn_{0.85}O Thin Films.....	411
Wei Wei, Vikram Bhosle, Chunming Jin, and Roger J. Narayan	
ZnO Nanofibers Doped With Ga, In and Er Fabricated With Electrospinning Technique.....	417
Aurangzeb Khan, Wojciech M. Jadwisienczak, Saima N. Khan, and Martin E. Kordesch	
Structural, Optical and Magnetic Properties of Co and Fe Doped ZnO Thin Films Grown by Radio Frequency Magnetron Sputtering.....	423
Luis M. Angelats, Maharaj S. Tomar, Rahul Singhal, Oscar P. Perez, Hector J. Jimenez, and Ricardo Martinez	
Lasing Characteristics of Nano-Structured Zinc Oxide.....	429
Shou-Yi Kuo, Wei-Chun Chen, and Fang-I Lai	
Author Index.....	435
Subject Index.....	439

PREFACE

Zinc Oxide and Related Materials (e.g. MgO, CdO) are drawing considerable interest in recent years worldwide due to their potential for applications in LEDs for solid-state lighting, UV lasers and detectors, transparent electronics, bio sensors, acoustic devices, high-temperature electronics, and space electronics due to radiation hardness of these materials. Symposium K, "Zinc Oxide and Related Materials," held November 27–30 at the 2006 MRS Fall Meeting in Boston, Massachusetts featured the first symposium on this subject. The symposium consisted of 15 invited papers, 79 contributed oral papers, and 113 poster presentations, featuring sessions covering topics on theory, bulk and epitaxial growth, characterization, doping, defects, heterostructures, quantum wells, quantum dots, nanowires, nanorods, nanopillars, electrical, optical and structural properties, processing, transparent conducting oxides, Ohmic contacts, Schottky diodes, light emitting diodes, lasers, photodetectors, surface acoustic wave devices, sensors, spintronics and magnetism, and thin-film transistors for large area displays. Symposium K was well attended with lively discussions on many topics of current interest. This proceedings volume features selected papers presented at the symposium giving an overview of research carried out in laboratories worldwide. The symposium drew an audience from universities, research institutions, Government laboratories, and industry.

We wish to thank all the invited speakers, session chairs, contributed oral and poster paper presenters and participants for making the symposium a grand success. We gratefully acknowledge the generous financial support of the Air Force Office of Scientific Research and the U.S. Army Research Office.

Jürgen Christen
Chennupati Jagadish
David C. Look
Takafumi Yao
Frank Bertram

February 2007

A Comparison of the Mechanical Properties and the Impact of Contact Induced Damage in *a*- and *c*- Axis ZnO Single Crystals

V. A. Coleman¹, J. E. Bradby¹, C. Jagadish¹, and M. R. Phillips²

¹Department of Electronic Materials Engineering, Research School of Physical Sciences and Engineering, The Australian National University, Canberra, 0200, Australia

²Microstructural Analysis Unit, University of Technology, Sydney, Broadway, 2007, Australia

ABSTRACT

Nanoindentation studies were conducted on *a*-axis oriented ZnO single crystals. The mechanical properties and deformation mechanisms were monitored and compared to previously determined data from *c*-axis material. Hardness and modulus values reveal that *a*-axis ZnO is significantly softer than *c*-axis material (hardness of 2 ± 0.2 GPa), and behaves more plastically. Additionally, the influence of contact induced damage on the defect structure of *a*-axis material was examined using cathodoluminescence spectroscopy and monochromatic imaging to monitor the luminescence from indent sites. Deformation directly under the indent site enhanced the occurrence of red luminescence, and was attributed to a native defect in ZnO that has a higher formation energy than the defects responsible for the green and yellow visible defect bands, which were present in ZnO during growth and clustered to the indent site during annealing.

INTRODUCTION

Semiconductor device processing involves extensive surface contact, and thus it is important to investigate how the active material is affected during device production. Orientation changes are known to dramatically influence the mechanical properties of single crystals [1]. In ZnO, both *a*- and *c*-axis orientations present attractive options for devices possessing different functionalities. Studying these effects in ZnO is thus of merit to give an insight into the critical issues and necessary sensitivities in ZnO device processing. *c*-axis ([0001]) oriented single crystal ZnO is already known to be an extremely soft [2] material that is highly susceptible to damage [3,4]. It has a hardness of only ~5 GPa [2] (for comparison, GaN has a hardness of ~15 GPa). Currently however, very little is known about the mechanical properties of *a*-axis ([11-20]) oriented ZnO.

Previously, nanoindentation studies of ZnO have focused on poly-crystalline [5,6] or single crystal *c*-axis oriented [2-4,7-10] samples. To the best of our knowledge, the mechanical properties of *c*-axis ZnO determined by Kucheyev *et. al.* [2] is the only work dealing with the mechanical properties of single crystal ZnO. The primary deformation mechanism in *c*-axis material is slip along the basal planes, indicated by the occurrence of multiple 'pop-in' discontinuities during loading [2]. Additionally, surface contact induces extensive deformation damage in *c*-axis ZnO single crystal samples, with a very large propagation of defects well beyond the volume under contact [4]. The production of these defects leads to the quenching of band edge luminescence and a simultaneous enhancement of defect emission in the visible band in characteristic rosette shapes, oriented along [11-20], [2-1-10] and [1-210] directions, and at

higher loads, star features which are offset to the rosettes by $<30^\circ$ along $[0-110]$, $[1-100]$ and $[-1010]$ directions [3, 4, 8,10].

In this paper, hardness and modulus measurements, deformation mechanisms and the impact of defects produced during indentation in *a*-axis ZnO are compared with previous results obtained on *c*-axis oriented material. This has been achieved using nanoindentation, XTEM, and cathodoluminescence (CL) spectroscopy and monochromatic imaging.

EXPERIMENT

The samples used in this study were commercially available single crystal samples purchased from MTI corp. (*a*-axis sample). Series of both continuous load and partial load-unload nanoindentations were made with an ultra micro indentation system (UMIS) 2000 up to a maximum load of 200 mN. All measurements were carried out in ambient conditions on cleaned and degreased samples with a spherical diamond indenter tip (radius $<4.3 \mu\text{m}$). Both the UMIS and the indenter tip were pre-calibrated using a fused silica standard with known material properties. The Field and Swain method of analysis [11] was used to extract hardness and elastic modulus values.

XTEM samples were prepared by focused ion beam (FIB) milling in a single-beam FEI xP200 FIB system with 30 keV Ga ions. XTEM images of 15 and 50 mN indents were taken on a Phillips CM300 transmission electron microscope, using an accelerating voltage of 300 kV. The influence of indentation on the defect structure of *a*-axis ZnO was studied in an array of 100 and 200 mN indents. The indents were spaced such that the damage caused by one indent would not effect the surrounding indents. From previous experience with this material system, it was expected that these loads would not induce cracking or phase transformations in the ZnO [1,3].

After indentation on four different pieces of ZnO, rapid thermal annealing was conducted at 400, 600 and 800 °C respectively for 60 s under an Ar ambient. This step was implemented to monitor the recovery of the indented regions with annealing temperature. The samples were then loaded into JEOL35C scanning electron microscope (SEM) fitted with an Oxford Instruments MonoCL2 system for CL spectroscopy and monochromatic imaging. The CL spectra and images were measured using a Hamamatsu R943-02 Peltier cooled photomultiplier tube and a 1200 lines/mm grating blazed at 500 nm. The accelerating voltage was 25 kV and all measurements were made at 77 K. All spectra were corrected for the system response of the detector.

DISCUSSION

Figure 1 shows load-unload curves from indents of various loads made in *a*-axis ZnO. There are two notable features in this figure. Firstly, for all loads, only one 'pop-in' event is seen, occurring reproducibly at very low loading force. This is quite different to *c*-axis ZnO in which multiple pop in events are seen, with no particular correlation to applied force. Secondly, the shape of the unloading curve indicates that *a*-axis ZnO does not recover from indentation well - that is to say this material behaves in a strongly plastic manner. In contrast, *c*-axis material displays greater elasticity upon unloading, and, although it does not experience a 'pop-out', the penetration depth recovers by approximately 30%. From load-unload curves alone, it appears

Figure 1: Load-unload curves of indents in *a*-axis ZnO. Only a single 'pop-in' event is seen in all cases. The inset shows the large single 'pop-in' event for clarity.

that *a*-axis material is soft, due to the relationship between penetration depth and applied force. To quantify this more precisely, it is necessary to extract hardness and modulus measurements from partial load-unload indentations. In Figure 2 below, hardness and modulus data from *a*-axis ZnO (triangles) is compared to measurements made on *c*-axis bulk material (circles). No work hardening is evident in either orientation, however a very clear difference can be seen between the hardness of the two orientations, with *a*-axis material (2 GPa) being significantly softer than *c*-axis material (5 GPa). This has significant implications for device processing of *a*-axis material. To understand the reason for these observed orientation differences, we turn to XTEM analysis of *a*-axis material

A bright field (BF) XTEM image of a 50 mN indent in *a*-axis ZnO is shown in figure 3. From this image, slip along the *c*-axis oriented basal plane which lies perpendicular to the surface of the sample can be clearly seen. This basal slip, as with *c*-axis material, is the primary

Figure 2: Hardness and modulus measurements comparing *a*- and *c*-axis bulk ZnO

Figure 3: BF XTEM image of a 50 mN indent in *a*-axis bulk ZnO. The arrow shows the direction of indentation. The Pt is in place to protect the surface during FIB milling.

mechanism for deformation in this system. The orientation of the basal plane in this case accounts for the occurrence of only one 'pop-in' event during loading, and also why the material behaves so plastically. The egg-timer shape evident in the image reflects the strain field induced in the ZnO during indentation. Secondary deformation by means of slip along the pyramidal planes is also evident in this image. These slip bands can be seen to propagate very far into the surrounding material, and were measured to propagate over 14 μm from the initial indent site, indicating that a large number of far-propagating defects are created by contact induced damage in this system.

CL spectroscopy and monochromatic imaging are two very useful tools for investigating the impact of defects introduced during indentation upon the luminescence from ZnO. Figure 4

Figure 4: SEM(top row) and CL monochromatic imaging of four indented *a*-axis samples taken at three wavelengths. The horizontal field width of each image is $\sim 170 \mu\text{m}$. The indents shown are for 100 and 200 mN loads.

shows monochromatic CL images taken at 3 different wavelengths of four *a*-axis ZnO samples annealed at different temperatures. At 390 nm (band edge of ZnO), clear quenching is observed. Unlike *c*-axis ZnO in which indentation results in quenching in a rosette and Star-of-David type pattern, in *a*-axis material 'bow-tie' quenching features are created. This difference in shape is due to the different orientation of the planes within the ZnO at this orientation. The 'arms' of the bow-tie follow the direction of the basal [0001] planes. With increasing annealing temperature, the 'bow-tie' becomes more well-defined and takes on a ~12 sided polygon type-shape. At 530 nm, there is significant defect luminescence present all over the sample from as-grown defects emitting in the yellow and green. It is interesting to note that this luminescence appears in streaks oriented along the [0001] direction. With annealing, luminescence around the indent site becomes evident, as the quenching around the indent site is recovered. The quenching evolves to form a ring around the indent site with an X forming through the indent, the arms of which extend along the [0001] direction at 800 °C.

In the case of the 650 nm images, the defect luminescence arising from the indents is much more obvious. At this wavelength, there is minimal luminescence from the bulk material, making the influence of the indents easier to examine. After indentation, most of the defect luminescence appears from outside the indent site, along the arms of the 'bow-tie' in the [0001] direction, and is concentrated in the pile-up region. With annealing, the defects migrate into the centre of the indent, correlating much more strongly with that of the quenched areas of the band edge emission. Similar observations were made for *c*-axis material; although in the case of *c*-axis material annealing at 800 °C appeared to recover the defects, whereas in *a*-axis material it enhances them. This may reflect different qualities of starting material.

The wavelength dependence of the pattern of luminescence suggests that at least two distinct defects are present in *a*-axis ZnO. This is reflected in figure 5. Like *c*-axis material, the defect responsible for the yellow and green luminescence (YL/GL) band appears to be native defects which are also present in the ZnO after growth, whereas the defect responsible for the red luminescence (RL) appears to arise more through the process of indentation itself, and may represent a native defect in ZnO with a higher formation energy.

Figure 5: CL spectra taken from the 600 °C annealed and indented sample at different positions around the indent. Horizontal field width was 89 μ m.

CONCLUSIONS

The hardness and modulus of *a*-axis single crystal ZnO were measured and found to be 2 ± 0.2 GPa and 163 ± 6 GPa respectively, indicating that *a*-axis ZnO is significantly softer and more plastic than *c*-axis material. Like *c*-axis material, the primary deformation mechanism is slip along the basal plane, followed by defect creation and propagation along pyramidal planes. The *c*-axis plane is basal in ZnO. In *a*-axis material this plane lies perpendicular to the surface. Thus deformation proceeds by one initial slip event along this plane which is reflected by a singular 'pop-in' discontinuity on loading, instead of the multiple 'pop-ins' seen for *c*-axis material.

As in *c*-axis material, indentation also results in band edge quenching around the indent site and enhancement of defect emission in the visible band, however this cannot be recovered through annealing in this sample. 'Bow-tie' features can be seen from CL mapping, with quenching observed at the band edge (390 nm) and clustering of the visible defect luminescence to specific sites in and around the indent site which become more defined with annealing. RL arises more strongly from the centre of the indent site, whilst GL and YL is already present in the sample and clusters to the edge of the indent site during annealing, similar to what was observed in *c*-axis ZnO. This suggests that in *a*-axis ZnO, the RL arises from a native defect with high formation energy, whilst the GL/YL arises from one or more native defects with very low formation energy, which are present/created during growth.

ACKNOWLEDGMENTS

The authors wish to thank the Australian Research Council for financial support.

REFERENCES

1. M. Y. Kahn, L. M. Brown and M. M. Chaduri, *J. Phys. D Appl. Phys.* **25**, A257 (1992).
2. S. O. Kucheyev, J. E. Bradby, J. S. Williams, C. Jagadish and M. V. Swain, *Appl. Phys. Lett.* **80**, 956 (2002).
3. V. A. Coleman, J. E. Bradby, C. Jagadish and M. R. Phillips, *Appl. Phys. Lett.*, **89**, 082102 (2006).
4. J. E. Bradby, S. O. Kucheyev, J. S. Williams, C. Jagadish, M. V. Swain, P. Munroe and M. R. Philips, *Appl. Phys. Lett.* **80**, 4537 (2002).
5. S. V. Prasad and J. S. Zabinski, *Wear* **203-204**, 498 (1997).
6. M. J. Mayo, R. W. Siegel, Y. X. Liao and W. D. Nix, *J. Mat. Res.* **7**, 973 (1992).
7. M. J. Klopstein, D. A. Lucca and G. Cantwell, *Phys. Stat. Sol.(a)* **196(1)**, R1 (2003).
8. Z. Takkouk, N. Brihi, K. Guergouri and Y. Marfaing, *Physica B* **366**, 185 (2005).
9. M. J. Klopstein and D. A. Lucca, *Appl. Phys. Lett.* **87**, 131 906 (2005).
10. J. T. Czernuszka and N. Pratt, *Phil. Mag. Lett.* **61(3)**, 83 (1990).
11. J. S. Field and M. V. Swain, *J. Mat.Res.* **8**, 297 (1993).